

# **BENZOIN SUMATRA RESINOID FIRMENICH 915034**

Revision date: 29-03-2023 Print Date: 26-04-2024 Version: 4.0/GHS/EN Page: 1 / 6

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

# 1.1. Identification of the substance/mixture

**Trade name: BENZOIN SUMATRA RESINOID FIRMENICH 915034** 

Substance name: BENZOIN RESINOID CAS Number: 9000-05-9, -**CF Number:** 232-523-7

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Raw material for the manufacture of fragrances and/or flavourings.

# 1.3. Details of the supplier of the safety data sheet

Ernesto Ventós SA Company: Address:

Carretera Real, 120 B

08960 Sant Just Desvern - Barcelona - SPAIN

Telephone: (00 34) 934 706 210 (00 34) 934 733 010 Fax: E-mail: info@ventos.com

#### 1.4. Emergency telephone number

NCEC (+44) 1865 407333 (24h) NCEC (+34) 91 114 2520 (24h) (ES)

NCEC (+1) 202 464 2554 (24h) (USA, Canada)

# 2. HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

Acute Toxicity - Category 5 (oral) - H303 Skin Irritant - Category 3 - H316 Serious eye damage - Category 1 - H318 Skin sensitizer - Category 1A - H317

Specific target organ toxicity following repeated exposure - Category 2 - H373 Hazardous to the aquatic environment, short-term (acute) - Category 3 - H402

## 2.2. Label Elements

# **Hazard pictograms:**







#### Signal Word:

Danger

## **Hazard statements:**

H303 - May be harmful if swallowed.

H316 - Causes mild skin irritation.

H317 – May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H373 - May cause damage to organs through prolonged or repeated exposure.

H402 - Harmful to aquatic life.

## **Precautionary statements:**

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352+P333+P313 – IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.



# **BENZOIN SUMATRA RESINOID FIRMENICH 915034**

#### 2.3. Other hazards

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1. Substances

Chemical name: BENZOIN RESINOID CAS number: 9000-05-9, - EC number: 232-523-7

#### **Hazardous constituents:**

Chemical Name	% (w/w)	CAS No. EC No.	Classification according to GHS	
CINNAMIC ACID	≥50	621-82-9 210-708-3	Acute Toxicity - Category 5 (oral) - H303 Skin Irritant - Category 3 - H316 Eye Irritant - Category 2A - H319 Specific target organ toxicity following repeated exposure - Category 2 - H373 Hazardous to the aquatic environment, short-term (acute) - Category 3 - H402	
BENZOIC ACID	≥1; <10	65-85-0 200-618-2	Acute Toxicity - Category 5 (oral) - H303 Skin Irritant - Category 2 - H315 Serious eye damage - Category 1 - H318 Specific target organ toxicity following repeated exposure - Category 1 - H372 Hazardous to the aquatic environment, short-term (acute) - Category 3 - H402	
VANILLIN	≥1; <10	121-33-5 204-465-2	Acute Toxicity - Category 5 (oral) - H303 Acute Toxicity - Category 5 (dermal) - H313 Eye Irritant - Category 2A - H319 Hazardous to the aquatic environment, short-term (acute) - Category 3 - H402	
BENZYL CINNAMATE	≥1; <10	103-41-3 203-109-3	Acute Toxicity - Category 5 (oral) - H303 Skin sensitizer - Category 1B - H317 Hazardous to the aquatic environment, short-term (acute) - Category 1 - H400 Hazardous to the aquatic environment, long-term (chronic) - Category 2 - H411	
ETHANOL	≥1; <10	64-17-5 200-578-6	Flammable Liquids - Category 2 - H225 Eye Irritant - Category 2A - H319	
CINNAMIC ALCOHOL	≥0.1; <1	104-54-1 203-212-3	Acute Toxicity - Category 4 (oral) - H302 Skin Irritant - Category 3 - H316 Skin sensitizer - Category 1B - H317 Hazardous to the aquatic environment, short-term (acute) - Category 2 - H401	
CINNAMIC ALDEHYDE	≥0.1; <1	104-55-2 203-213-9	Acute Toxicity - Category 4 (dermal) - H312 Acute Toxicity - Category 5 (oral) - H303 Skin Irritant - Category 2 - H315 Eye Irritant - Category 2A - H319 Skin sensitizer - Category 1A - H317 Hazardous to the aquatic environment, short-term (acute) - Category 2 - H401 Hazardous to the aquatic environment, long-term (chronic) - Category 3 - H412	

See the full text of the hazard statements in section 16.

# 3.2. Mixtures

Not applicable.

# 4. FIRST-AID MEASURES

# 4.1. Description of necessary first aid measures

Ingestion: Rinse mouth with water.

Obtain medical advice.

Keep at rest. Do not induce vomiting.

Eye contact: In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes and seek medical advice.

Inhalation: Remove person to fresh air and keep at rest. Seek immediate medical advice.

Skin contact: Take off immediately all contaminated clothing.

Thoroughly wash affected skin with soap and water.

Seek medical attention if symptoms persist.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

No information available.



# **BENZOIN SUMATRA RESINOID FIRMENICH 915034**

# 5. FIRE-FIGHTING MEASURES

## 5.1. Extinguishing Media

Water spray, carbon dioxide, dry chemical powder or appropriate foam. For safety reasons do not use full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Known or Anticipated Hazardous Products of Combustion: Emits toxic fumes under fire conditions.

#### 5.3. Advice for firefighters

High temperatures can lead to high pressures inside closed containers.

Avoid inhalation of vapors that are created. Use appropriate respiratory protection.

Do not allow spillage of fire to be poured into drains or watercourses.

Wear self-contained breathing apparatus and protective clothing.

## **6. ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate surronding areas. Ensure adequate ventilation. Keep unnecessary and unprotected personnel from entering. Do not breathe vapor/spray. Avoid contact with skin and eyes. Information regarding personal protective measures: see section 8.

### 6.2. Environmental precautions

To avoid possible contamination of the environment, do not discharge into any drains, surface waters or groundwaters.

# 6.3. Methods and materials for containment and cleaning up

 $Cover\ with\ an\ inert, inorganic, non-combustible\ absorbent\ material\ (e.g.\ dry-lime, sand, soda\ ash).$ 

Place in covered containers using non-sparking tools and transport outdoors.

Avoid open flames or sources of ignition (e.g. pilot lights on gas hot water heater).

Ventilate area and wash spill site after material pickup is complete.

#### 6.4. Reference to other sections

Information regarding exposure controls, personal protection and disposal considerations can be found in sections 8 and 13.

# 7. HANDLING AND STORAGE

# 7.1. Precautions for safe handling

Do not store or handle this material near food or drinking water. Do not smoke.

Avoid contact with the eyes, skin and clothing. Wear protective clothing and use glasses.

Observe the rules of safety and hygiene at work.

Keep in the original container or an alternative made from a compatible material.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed and preferably full containers in a cool, dry and ventilated area, protected from light.

Keep away from sources of ignition (e.g. hot surfaces, sparks, flame and static discharges).

Keep away from incompatible materials (see section 10).

# 7.3. Specific end use(s)

No information available.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### 8.1. Control parameters

Components with occupational exposure limits:

Chemical Name	CAS No.	Norm.	8 hr.			15 min.		
Chemical Name			5 iii.	ppm	mg/m³	15 111111.	ppm	mg/m³
BENZOIC ACID	65-85-0	DE (Deutschland)	AGW	0.1	0.5	AGW		
		DE (Deutschland)	AGW	200	380	AGW		
		ES (España)	VLA-ED			VLA-EC	1	1.91
ETHANOL	64-17-5	FR (France)	VME	1000	1900	VLCT	5000	9500
		UK (United Kingdom)	Workplace exposure limit	1000	1920	Workplace exposure limit		
		OSHA	PEL-TWA	1000	1900	PEL-STEL		



# **BENZOIN SUMATRA RESINOID FIRMENICH 915034**

Revision date: 29-03-2023 Print Date: 26-04-2024

Version: 4.0/GHS/EN Page: 4 / 6

 			•••	•••		
	Cal OSHA	PEL-TWA	1000	1900	PEL-STEL	

### 8.2. Exposure controls

Measures should be taken to prevent materials from being splashed into the body.

Provide adequate ventilation, according to the conditions of use. Use a mechanical exhaust if required.

## 8.3. Individual protection measures, such as personal protective equipment

Eye/Face protection: Chemical safety goggles are recommended. Wash contaminated goggles before reuse. Hand Protection: Chemical-resistant gloves are recommended. Wash contaminated gloves before reuse.

Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks

involved.

Respiratory Protection: In case of insufficient ventilation, use suitable respiratory equipment.

Emissions from ventilation or process equipment should be checked to ensure they comply with environmental Environmental exposure controls:

protection legislation.

In some cases, filters or engineering modifications to the process equipment will be necessary to reduce emissions to

acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Solid Appearance:

Colour: Conforms to standard Odour: Conforms to standard Odour theshold: Not determined рН: Not determined Melting point/freezing point: Not determined Boling point/boiling range (°C): Not determined

Flash point: 101 °C

Evaporation rate: Not determined Flammability: Not determined Lower flammability/Explosive limit: Not determined Upper flammability/Explosive limit: Not determined Vapour pressure: 13.33226 Pa Vapour Density: Not determined Density: Not determined Relative density: Not determined Water solubility: INSOLUBLE IN WATER Solubility in other solvents: **SOLUBLE IN ETHANOL** Partition coefficient n-octanol/water: Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined Viscosity, dynamic: Not determined Viscosity, kinematic: Not determined Explosive properties: Not determined NONE EXPECTED Oxidising properties:

# 10. STABILITY AND REACTIVITY

#### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

## 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

## 10.4. Conditions to Avoid

Conditions to Avoid: Excessive heat, flame or other ignition sources.

## 10.5. Incompatible materials

Avoid contact with strong acids and bases and oxidizing agents.

## 10.6. Hazardous decomposition products

During combustion may form carbon monoxide and unidentified organic compounds.



# **BENZOIN SUMATRA RESINOID FIRMENICH 915034**

# 11. TOXICOLOGICAL INFORMATION

Acute toxicity	May be harmful if swallowed.
Skin corrosion/irritation	Causes mild skin irritation.
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Based on the data available, the criteria for classification are not met.
Carcinogenicity	Based on the data available, the criteria for classification are not met.
Reproductive toxicity	Based on the data available, the criteria for classification are not met.
STOT-single exposure	Based on the data available, the criteria for classification are not met.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on the data available, the criteria for classification are not met.

# 12. ECOLOGICAL INFORMATION

## 12.1. Toxicity

**Assessment:** 

Harmful to aquatic life.

Experimental/calculated data:

No information available.

# 12.2. Persistence and degradability

No information available.

# 12.3. Bioaccumulative potential

No information available.

### 12.4. Soil mobility

No information available.

## 12.5. Other adverse effects

See also sections 6, 7, 13 and 15

Do not allow to get into waste water or waterways.

## 13. DISPOSAL CONSIDERATIONS

# 13.1. Waste treatment methods

Dispose of in accordance with national and local environmental regulations.

# 14. TRANSPORT INFORMATION

	ADR/RID/ADN	IMDG	IATA-ICAO
14.1. UN Number	Not classified as hazardous goods	Not classified as hazardous goods	Not classif <mark>ied as hazardous g</mark> oods
14.2. UN Proper Shipping Name	Not applicable	Not applicable	Not applicable
14.3. Transport Hazard Class(es)	Not applicable	Not applicable	Not applicable
14.4. Packing Group	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards	No	No	No
Additional information			

## 14.6 Special precautions for user

None known

# 14.7. Maritime transport in bulk according to IMO instruments

No information available

# 15. REGULATORY INFORMATION

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No information available

# **16. OTHER INFORMATION**

Full text of the R-phrases, hazard statements and precautionary statements mentioned in section 3:

H225 - Highly flammable liquid and vapour.

H302 - Harmful if swallowed.



# **BENZOIN SUMATRA RESINOID FIRMENICH 915034**

H303 – May be harmful if swallowed.

H312 – Harmful in contact with skin.

H313 - May ne harmful in contact with skin.

H315 – Causes skin irritation.

H316 – Causes mild skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H319 - Causes serious eye irritation.

H372 - Causes damage to organs through prolonged or repeated exposure.

H373 – May cause damage to organs through prolonged or repeated exposure.

H400 - Very toxic to aquatic life.

H401 – Toxic to aquatic life.

H402 – Harmful to aquatic life.

H411 – Toxic to aquatic life with long lasting effects.

H412 – Harmful to aquatic life with long lasting effects.

The information included in this safety data sheet is based on the available data at the moment this document is issued. It is meant to be a description of safety requirements for our product and does not stand for a guarantee of its properties. The user is responsible for taking all necessary steps leading to compliance with local rules and legislation.