

## **SPECIFICATION SHEET**

**VERSION** 1,00 **VERSION DATE** 05/04/22 **PRINT DATE** 29/04/24

PRODUCT PROPIONALDEHYDE NATURAL EU BESTALLY
APPLICATIONS Industrial raw material not intended for direct use.

IUPAC NAME PROPANAL

SYNONYMS PROPIONALDEHYDE, PROPANAL, PROPIONIC ALDEHYDE, ALDEHYDE C-3

 FORMULA
 C3 H6 O

 MOLECULAR WEIGHT
 58,08

 CAS
 123-38-6

**EINECS** 204-623-0

**FEMA** 2923

**TARIFF NUMBER** 2912190000

FOOD GRADE CERTIFICATE AVAILABLE ON REQUEST

**REACH REGISTRATION NO.** Exempt from registration (imported/manufactured < 1 ton/year)

**SPECIFICATIONS** 

ASPECT AT 20°C CLEAR MOBILE LIQUID

**COLOUR** COLOURLESS

ODOURALCOHOLIC,WINE,COCOA,NUTTY,COGNACTASTEMUSTY,YEAST,NUT,VEGETABLE,POTATO

 DENSITY AT 20°C (g / ml)
 0,801
 - 0,808

 DENSITY 25/25
 0,800
 - 0,805

 REFRACTIVE INDEX nD20
 1,3610
 - 1,3660

 REFRACTIVE INDEX nD25

OPTICAL ROTATION (°)

**BOILING POINT (°C)** 47,6°C (1003,27 hPa)

 MELTING POINT (°C)
 CA. -81°C

 FLASH POINT (°C)
 -30,00

 ASSAY (% GC)
 > 98

 ACID VALUE (mg KOH/g)
 < 5</td>

**SOLUBILITY** SOLUBILITY IN WATER: 306 g/L (25°C)

**VAPOUR PRESSURE** 400,46 hPa (23,6°C) **OTHER SOLUBILITIES** SOLUBLE IN ETHANOL

OTHER TECHNICAL DATA

SENSITIVE TO AIR AND MOISTURE. IT POLYMERIZES EASILY. IT OXIDIZES

FASTLY WITH OXIGEN OF THE AIR OPEN THE PRIM CAREFULLY AND SHOWLY

EASILY WITH OXIGEN OF THE AIR. OPEN THE DRUM CAREFULLY AND SLOWLY.

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 9 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

KEEP REFRIGERATED 2-8°C AND HEADSPACE PURGED WITH NITROGEN.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.

THIS PRODUCT HAS NOT BEEN FILTERED DUE TO TECHNICAL REASONS. WE RECOMMEND NOT TO USE IT UNLESS FILTERED WHEN USED AS A RAW MATERIAL IN FOOD INTENDED FOR FINAL CONSUMERS.