

SPECIFICATION SHEET

VERSION 1,00 **VERSION DATE** 30/01/20 **PRINT DATE** 20/04/24

PRODUCT BUDDHAWOOD OIL, AUSTRALIAN

APPLICATIONS Industrial raw material not intended for direct use.

IUPAC NAMEBUDDHAWOOD OILPLANT OF ORIGINEremophila mitchellii

PART OF THE PLANT WOOD

SYNONYMS

CAS 1429902-59-9

CAS 2 -EINECS -EINECS 2 --

TARIFF NUMBER 3301294900

REACH REGISTRATION NO.

SPECIFICATIONS

ASPECT AT 20°C MOBILE LIQUID

COLOUR REDDISH BROWN TO BROWN

ODOUR WOODY, SWEET, OAK

TASTE

DENSITY AT 20°C (g / ml) 0,990 - 1,050

DENSITY 25/25

REFRACTIVE INDEX nD20 1,5100 - 1,5400

REFRACTIVE INDEX nD25
OPTICAL ROTATION (°)
/

BOILING POINT (°C)

MELTING POINT (°C)

FLASH POINT (°C) 101,00

ASSAY (% GC)

ACID VALUE (mg KOH/g) -

SOLUBILITYINSOLUBLE IN WATERVAPOUR PRESSURENOT DETERMINEDOTHER SOLUBILITIESSOLUBLE IN ETHANOL

OTHER TECHNICAL DATA

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.