

SPECIFICATION SHEET

VERSION 1,00 **VERSION DATE** 19/09/22 **PRINT DATE** 28/04/24

PRODUCT KARMAWOOD IFF

APPLICATIONS Industrial raw material not intended for direct use.

IUPAC NAME 2,2,6-TRIMETIL-ALFA-PROPIL-CICLOHEXANEPROPANOL

SYNONYMS 1-(2,2,6-TRIMETHYLCYCLOHEXYL)-HEXAN-3-OL,KARMAWOOD,NORLIMBANOL

OH

 FORMULA
 C15 H30 O

 MOLECULAR WEIGHT
 226,00

 CAS
 70788-30-6

 CAS 2
 253454-23-8

 EINECS
 274-892-7

FEMA -

TARIFF NUMBER 2906190090

REACH REGISTRATION NO. 01-2120766836-38

SPECIFICATIONS

ASPECT AT 20°C CLEAR LIQUID / SOLID

COLOUR COLORLESS TO PELE YELLOW ODOUR WOODY, AMBER, SANDALWOOD

TASTE

DENSITY AT 20°C (g / ml) 0,894 - 0,902

DENSITY 25/25

REFRACTIVE INDEX nD20 1,4680 - 1,4740

REFRACTIVE INDEX nD25
OPTICAL ROTATION (°)
/

BOILING POINT (°C) MELTING POINT (°C) -

FLASH POINT (°C) 104,00

ASSAY (% GC) SUM OF ISOMERS > 95%

ACID VALUE (mg KOH/g) -

SOLUBILITY INSOLUBLE IN WATER
VAPOUR PRESSURE NOT DETERMINED
OTHER SOLUBILITIES SOLUBLE IN ETHANOL

OTHER TECHNICAL DATA

STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE. IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.