

## SPECIFICATION SHEET


**VERSION** 3,00 **VERSION DATE** 19/09/22 **PRINT DATE** 18/05/24

**PRODUCT** ETHYL LINOLEATE  
**APPLICATIONS** Industrial raw material not intended for direct use.  
**IUPAC NAME** ETHYL CIS,CIS-9,12-OCTADECADIENOATE  
**SYNONYMS** ETHYL LINOLATE, ETHYL CIS,CIS-9,12-OCTADECADIENOATE

**FORMULA** C20 H36 O2  
**MOLECULAR WEIGHT** 308,50  
**CAS** 544-35-4

**EINECS** 208-868-4

**FEMA** -  
**TARIFF NUMBER** 2916150000



**REACH REGISTRATION NO.** Exempt from registration (imported/manufactured < 1 ton/year)

## SPECIFICATIONS

<b>ASPECT AT 20°C</b>	MOBILE LIQUID (TURBID AT LOW TEMPERATURES)/SOLID	
<b>COLOUR</b>	COLORLESS TO YELLOW	
<b>ODOUR</b>	OILY	
<b>TASTE</b>		
<b>DENSITY AT 20°C (g / ml)</b>	0,865	- 0,890
<b>DENSITY 25/25</b>	-	
<b>REFRACTIVE INDEX nD20</b>	1,4450	- 1,4650
<b>REFRACTIVE INDEX nD25</b>	-	
<b>OPTICAL ROTATION (°)</b>	/	
<b>BOILING POINT (°C)</b>	224°C APPROX. (17 mm Hg)	
<b>MELTING POINT (°C)</b>	-	
<b>FLASH POINT (°C)</b>	101,00	
<b>ASSAY (% GC)</b>	> 50	
<b>ACID VALUE (mg KOH/g)</b>		
<b>SOLUBILITY</b>	INSOLUBLE IN WATER	
<b>VAPOUR PRESSURE</b>	NOT DETERMINED	
<b>OTHER SOLUBILITIES</b>	SOLUBLE IN ETHANOL	

## OTHER TECHNICAL DATA

## STABILITY AND STORAGE

KEEP IN TIGHTLY CLOSED CONTAINER IN A COOL AND DRY PLACE, PROTECTED FROM LIGHT. WHEN STORED FOR MORE THAN 24 MONTHS, QUALITY SHOULD BE CHECKED BEFORE USE.  
SOLID MATTER CAN APPEAR, OR TURBID PRODUCT WITH COLD. HEAT GENTLY AND/OR FILTER IF NECESSARY.

WE BELIEVE THE ABOVE INFORMATION TO BE CORRECT BUT WE DO NOT PRESENT IT AS ALL INCLUSIVE AND AS SUCH SHOULD BE USED AS A GUIDE.  
IT IS THE SOLE RESPONSIBILITY OF THE RECEIVER OF OUR PRODUCT TO COMPLY WITH EXISTING REGULATIONS AND INSTRUCTIONS.